



CLEANGO - Mobiele Afzuigunit



CLEANGO - Mobiele stof- en rookafzuigunit voor werkplaatsen

De CLEANGO is een mobiele afzuigunit ideaal voor periodiek stof- en rookafzuigen in werkplaatsen. Met flexibele Dynaflex afzuigarmen van 2 of 3 meter biedt de unit gebruiksgemak en minimale weerstand bij positioneren. De filtermonitor optimaliseert prestaties door de filterverzadiging te meten, en er is een muuruitvoering (CLEANGO WALL) voor vaste installatie beschikbaar.

Technische Specificaties





Technical features		CleanGo
Power	kW	1,1
Nominal air flow	m ³ /h	1400
Air flow capacity at arm Ø160	m ³ /h	1000
Number of Arms Dynaflex	mm 3 mt	1 x Ø160
Number of cartridges	Ø325mm H 400mm	1
Filtering Surface	m ²	12
Cartridge classification		
R.P.M.		2846
STD power supply	V Hz	230/400 50
Noise level	dB	72
Total weight	kg	80



DUTCH AIRWORKS PRODUCT BLAD

Afmetingen

MODEL	DIMENSIONS (mm)			
	A	B	C	D
CleanGo	760	700	843	916



Werking

CleanGo



POLLUTED AIR



FILTERED AIR

- ① Dusty air inlet
- ② Fan
- ③ Filter cartridges
- ④ Filtered air outlet
- ⑤ Hour counter
Run/stop switch
- ⑥ Pentapolar socket