



WALLY - Afzuigwand



WALLY - Afzuigwand

De Wally afzuigwand van Dutch Airworks is een compacte, efficiënte oplossing voor lasrook (W-versie) en slijpsel (G-versie). Uitklapbare platen optimaliseren de afzuiging, terwijl een krachtige ventilator zorgt voor effectieve zuigkracht. De Wally G bevat een vonkdover en automatische persluchtreiniging, wat zorgt voor langdurige filterwerking en een veilige, schone werkomgeving.

Technische Specificaties

Model	Filter Type	Version	Cartridges (nr)	Cartridge height (mm)	Cartridge diameter (mm)	Filter material	IFA/BGIA Classification	Fan	Voltage (V)	Frequency (Hz)	Nr Tanks	Tank Volume (lt)
WALLY DF/W 2.2 >	Cartridges	For welding	2	400	325	Polyester	M-PES	PRM 250	400	50	2	40
WALLY DF/G 2.2 >	Cartridges	For grinding	2	400	325	Polyester	M-PES	PRM 250	400	50	2	48

Model	Filter surface area (sqm)	Maximum flow rate (m3/h)	Maximum flow rate (cfm)	Revolutions (rpm)	Power (kW)
WALLY DF/W 2.2 >	16	2280	1345	2845	2.2
WALLY DF/G 2.2 >	16	2280	1345	2845	2.2



DUTCH AIRWORKS PRODUCT BLAD

Afmetingen

Model	Length (mm)	Height (mm)	Width (mm)	Weight (kg)
<u>WALLY DF/W 2.2</u> >	1410	1425	1950	230
<u>WALLY DF/G 2.2</u> >	1410	1425	1950	165

